




## Telephone: 5133 9958 www.ssequipmenthire.com.au

## WOBILE SCAFFOLD ERECTION GUIDE







- 7. The working deck must be two transoms from the top of the scaffold, at this point two horizontal braces are clipped onto the top transoms in a horizontal plane with a further two horizontals clipped to the next transoms down creating a 500mm mid rail.
- 8. If the working height exceeds 3 times the least base dimension, then outriggers must be fitted.
- **9.** All 700mm wide scadd must be fitted with outriggers or external wall ties.



- **5**. Attach two diagonal braces (blue braces) to the base unit as shown. Level the unit using adjustable legs. Check with spirit level, the base is now complete.
- **6.** For the next stage insert next riser frames onto spigots of the base frame. Continue the pattern of Diagonal Braces, (a new diagonal brace starts where the one beneath finishes and rises two transoms) this pattern carries on up to the working deck



- **10.** Attach ladder to the inside of the scaffold, ensure that the ladder is at a 65° to 75° angle in comparison to the deck and that the standoff is secured at the corresponding rung on the base fram. Always climb the scaffold from the internal ladder.
- 11. Fit toe boards to work platform.



**12.** Scaffold Towers where the platform is 4.0m or greater must be erected by ticketed scaffolder.